

## MATERIAL SAFETY DATA SHEET

### SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

**Product identifier:** METAL-SAFE

**Chemical family:** Mixture of amide solvent, surfactants, alcohol and terpenes.

**Product use:** Specialty Graffiti Remover for Metal Surfaces.

**Supplier name and address:**

**BK Enterprises**

3970 Youngfield Street

Wheat Ridge, CO, U.S.A. 80033

Phone: 303-865-8800 (7:30 AM to 4:30 PM, Monday to Friday, MST)

**Emergency Tel.#:** CHEM-TEL – North America 1-800- 255-3924 or Worldwide Intl. + 01- 813-248-0585

### SECTION 3 — HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Clear to pale yellow liquid, mild, lemon-like odor.

Warning! Causes eye irritation. May cause allergic skin reaction. Harmful if swallowed. May cause skin and respiratory tract irritation. Could cause headache, drowsiness or other effects to the central nervous system. Contains material which may cause adverse liver effects. Not reactive. Release to the environment may cause harm.

\*\*\*POTENTIAL HEALTH EFFECTS\*\*\*

**Target organs:** Eyes, skin, respiratory system, digestive system, liver, central nervous system.

**Routes of exposure:** Skin contact, skin absorption, eye contact, inhalation, ingestion.

**Signs and symptoms of short-term (acute) exposure:**

*Inhalation:* Harmful if inhaled. Inhalation may cause irritation to the nose, throat and upper respiratory tract.

Inhalation could also cause fatigue, difficulty breathing, dizziness, headache, drowsiness, nausea, vomiting and other central nervous system effects.

*Skin:* Direct contact with skin may cause moderate irritation. Product may be absorbed.

*Eyes:* Direct contact with eyes may cause severe irritation and possibly eye injury. Vapors are irritating to the eyes.

*Ingestion:* If ingested, may cause irritation to the mouth, throat and stomach. Symptoms may include dizziness, headache, drowsiness, nausea, vomiting and other central nervous system effects. This product may present an aspiration hazard. Aspiration into the lungs following ingestion may cause life-threatening lung injury.

**Chronic effects:** Repeated or prolonged exposure may result in severe drying, cracking and defatting of the skin (dermatitis). Prolonged or repeated exposure may cause adverse liver and nervous system effects.

**Carcinogenic status:** See TOXICOLOGICAL INFORMATION, Section 11.

**Additional health hazards:** May cause allergic skin reaction. Possible birth defect hazard. For further information, see TOXICOLOGICAL INFORMATION, Section 11.

**Potential environmental effects:** See ECOLOGICAL INFORMATION (Section 12).

### SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	% w/w
Alkyl Alcohol Salt	Proprietary	5-10%
Cycloalkane	Proprietary	5-10%
Ethanol	64-17-5	10-30%
Surfactant	Proprietary	10-30%
n-Methyl-2-Pyrrolidone	872-50-4	30-60%

NOTE (1): ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2004 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. This material is classified as hazardous under OSHA regulations (29CFR 1910.1200).

#### SECTION 4 — FIRST AID MEASURES

**Inhalation:** If inhaled, immediately remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical attention if adverse effect continues after removal to fresh air.

**Skin contact:** Immediately remove contaminated clothing and shoes. Wash skin thoroughly with mild soap and running water. Obtain medical attention if irritation persists. Launder clothing before reuse.

**Eye contact:** Immediately flush eyes with running water for a minimum of 15 minutes. Obtain medical attention immediately if adverse effect continues after flushing.

**Ingestion:** DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain medical attention immediately. Guard against aspiration into the lungs.

**Conditions aggravated by exposure:** May aggravate pre-existing skin, eye and respiratory problems.

**Recommendations to physicians:** Treat symptoms and eliminate overexposure.

#### SECTION 5 — FIRE FIGHTING MEASURES

**Fire hazards/conditions of flammability:** May be combustible under certain conditions. This material may ignite when exposed to extreme heat and direct flame. Vapors are heavier than air and will collect in low-lying areas and confined spaces. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

**Flammability classification (OSHA 29 CFR 1910.1200):** Class IIIB Combustible Liquid.

**Flash point:** 95°C / 203°F

**Auto-ignition temperature:** N/Av

**Oxidizing properties:** None known

**Lower flammable limit (% by vol.):** N/Av

**Upper flammable limit (% by vol.):** N/Av

**Explosion data:**

*Sensitivity to mechanical impact:* May be sensitive to static discharge.

*Sensitivity to static discharge:* Not sensitive.

**Suitable extinguishing media:** Use foam, dry chemical, carbon dioxide or water spray / fog. Do not use water jet.

**Special fire-fighting procedures/equipment:** Firefighters should wear proper protective equipment and respiratory protection as conditions warrant. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and containers exposed to heat and flame. Avoid spreading burning liquid with water spray used for cooling purposes.

**Hazardous combustion products:** Carbon oxides, nitrogen oxides, sulfur oxides and other irritating fumes and smoke.

#### SECTION 6 — ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate chemically protective equipment. Keep all other personnel upwind and away from the spill/release. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

**Environmental precautions:** Ensure spilled product does not enter drains, sewers or confined spaces. Dike far ahead of large spills with non-combustible, inert absorbent material.

**Spill response/Cleanup:** Eliminate all sources of ignition. Ventilate area of release. Stop leak if you can do so without risk. Use non-sparking tools. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand, earth), then place absorbent material into a suitable container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

**Prohibited materials:** None known.

**Special spill response procedures:** If a spill/release in excess of EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).

DOT/CERCLA Reportable quantity (RQ): Sodium dodecylbenzenesulfonate (RQ 1000 lbs.)

#### SECTION 7 — HANDLING AND STORAGE

**Safe handling procedures:** This material is a harmful liquid. Wear appropriate protective equipment during handling. Use in a well-ventilated area. Avoid inhalation of vapors. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Keep away from heat and flame. Keep away from acids and other incompatible materials. Use caution when opening cap. Keep container tightly closed when not in use. Assume empty containers contain residues, which are hazardous.

**SECTION 7 — HANDLING AND STORAGE (Continued)**

**General hygiene considerations:** Avoid inhalation of vapors and mists. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when working. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

**Storage requirements:** Store in a cool, dry, well-ventilated area away from sources of heat, ignition and sunlight. Keep away from incompatibles and flammable materials. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Containers should be separated from oxidizing materials by a minimum distance of 20 ft. or by a barrier of non-combustible material at least 5 ft. high having a fire-resistance rating of at least 0.5 hours. Refer to NFPA 30, *Flammable and Combustible Liquids Code*, for additional information on storage. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

**Special packaging materials:** Always keep in containers made of the same materials as the supply container.

**SECTION 8 — EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**Ventilation and engineering controls:** Use in well-ventilated area. Local mechanical exhaust / extraction ventilation may be required if used indoors on a continuous basis.

**Exposure Limits:**

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR							OTHER mg/m <sup>3</sup>
		ACGIH-TLVs		OSHA-PELs		NIOSH-RELs		NIOSH	
		TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	IDLH mg/m <sup>3</sup>	
Proprietary Alkyl Alcohol Salt		NE	NE	NE	NE	NE	NE	NE	NE
Proprietary Cycloalkane		NE	NE	NE	NE	NE	NE	NE	DFG MAKs: Danger of Sensitization of the Skin TWA = 110 PEAK = 2•MAK 15 min. average value, 1-hr interval, 4 per shift DFG MAK Pregnancy Risk Classification: C
Ethanol	64-17-5	1800	NE	1900	NE	1900	NE	3000 ppm (based on 10% of LEL)	DFG MAKs: TWA = 900 PEAK = 2•MAK 15 min. average value, 1-hr interval, 4 per shift DFG MAK Pregnancy Risk Classification: C DFG MAK Germ Cell Mutagen Category: 5
n-Methyl-2-Pyrrolidone	872-50-4	NE	NE	NE	NE	NE	NE	NE	DFG MAKs: TWA = 82 (vapor) skin PEAK = 2•MAK 15 min. average value, 1-hr interval, 4 per shift DFG MAK Pregnancy Risk Classification: C AIHA WEELS: TWA = 10 ppm (skin)
Proprietary Surfactant		NE	NE	NE	NE	NE	NE	NE	NE

NE = Not Established.

**Respiratory protection:** Respiratory protection is required if airborne concentrations are above recommended TLVs or are not known. If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134) or equivalent U.S. State standards, and the Canadian CSA Standard Z94.4-02, *Selection, Care and Use of Respirators*. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, in emergency situations or when oxygen levels are unknown, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

**Hand protection:** It is recommended that protective gloves impervious to the material be worn at all times during use. Use triple gloves for spill response. If necessary, refer to U.S. OSHA 29 CFR 1910.138 and appropriate standards of Canada.

## SECTION 8 — EXPOSURE CONTROLS AND PERSONAL PROTECTION (Continued)

**Eye / face protection:** Use chemical splash goggles when a potential for eye contact exists. A full face shield should be worn when handling more than 1 gallon of product. If necessary, refer to U.S. OSHA 29 CFR 1910.133, the Canadian CSA Standard Z94.3-02, *Industrial Eye and Face Protection*. An eyewash station and safety shower should be made available in the immediate working area.

**Skin protection and other protective equipment:** Use body protection appropriate for task. An apron, or other impermeable body protection is suggested. Full-body chemical protective clothing is recommended for emergency response procedures. If necessary, refer to the OSHA Technical Manual (Section VII: Personal Protective Equipment), or appropriate Standards of Canada. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136 and the Canadian CSA Standard Z195-02, *Protective Footwear*. An eyewash station and safety shower should be made available in the immediate working area.

## SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

**Physical state, odor and appearance:** Clear to pale yellow liquid, mild, lemon-like odor.

**Specific gravity:** Not established.

**Volatiles (% by weight):** Not established.

**Vapor density (Air = 1):** Not established.

**Freezing point:** Not established.

**Evaporation rate (n-Butyl acetate = 1):** Not established.

**Solubility in water:** Miscible.

**Vapor pressure (PSIG):** Not established.

**Boiling point:** Not established.

**pH:** Not established.

## SECTION 10 — REACTIVITY AND STABILITY DATA

**Stability and reactivity:** Stable under the recommended storage and handling conditions prescribed.

**Hazardous polymerization:** Will not occur.

**Conditions to avoid:** Avoid sources of heat, flame, and direct sunlight.

**Materials to avoid (incompatibles):** Acids, bases, strong oxidizing agents.

**Hazardous decomposition products:** *Combustion:* Carbon oxides, nitrogen oxides, sulfur oxides. *Hydrolysis:* None known. On exposure to air, product may slowly polymerize. This process is accelerated by direct sunlight.

## SECTION 11 — TOXICOLOGICAL INFORMATION

**Toxicological data:** There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data for components in 1% concentration or greater. Additional data is available, but is not presented in this MSDS. Contact BK Enterprises for more information.

<b>Ingredients</b>	<b>LC<sub>50</sub>(4hr)</b>	<b>LD<sub>50</sub> (mg/kg)</b>	<b>LD<sub>50</sub> (mg/kg)</b>
	<b>inhalation, rat</b>	<b>oral, rat</b>	<b>dermal, rabbit</b>
Proprietary Cycloalkane	Not established	4400	> 5000
Ethanol	20,000 ppm / 10 hrs	760	Not established.
n-Methyl-Pyrrolidone	Not established	3914	8000
Proprietary Surfactant	Not established	438	Not established.

**Carcinogenicity:** Components of this product are listed by agencies tracking the carcinogenic potential of chemical compounds, as follows:

**Proprietary Alkyl Alcohol Salt:** ACGIH TLV-A4 (Not Classifiable as a Human Carcinogen)

**Proprietary Cycloalkane:** IARC-3 (Unclassifiable as to Carcinogenicity in Humans); MAK-5 (Substances with carcinogenic and genotoxic effects, the potency of which is considered to be so low that, provided the MAK and BAT values are observed, no significant contribution to human cancer is to be expected.)

**Ethanol:** ACGIH TLV-A4 (Not Classifiable as a Human Carcinogen); MAK-5 (Substances with carcinogenic and genotoxic effects, the potency of which is considered to be so low that, provided the MAK and BAT values are observed, no significant contribution to human cancer is to be expected.)

None of the remaining ingredients listed are classified by IARC, ACGIH, NTP, MAK, EPA, NIOSH or OSHA as carcinogenic.

**Reproductive effects, Teratogenicity, Mutagenicity:** This product contains n-Methyl-2-Pyrrolidone. This material may cause embryotoxic and teratogenic effects, based on animal data. These effects were noted following doses which were administered by injection (intraperitoneal), or following doses which were maternally toxic and were administered dermally. The Proprietary Alkyl Alcohol Salt component may be a potential developmental hazard by ingestion. It is known to cause mutations to germ cells and somatic cells in animals. In addition, this material causes embryotoxicity, fetotoxicity and teratogenicity in animals, in the presence of maternal toxicity.

## SECTION 11 — TOXICOLOGICAL INFORMATION (Continued)

**Reproductive effects, Teratogenicity, Mutagenicity (continued):** This product contains Ethanol, which is a known human reproductive toxin when ingested as alcoholic beverages. No reproductive effects have been reported following Ethanol exposure in the workplace. It is known to cause mutations to germ cells and somatic cells in animals. In addition, this material causes embryotoxicity, fetotoxicity and teratogenicity in animals, in the presence of maternal toxicity.

**Sensitization to material:** Due to the presence of Proprietary Cycloalkane, this product may cause an allergic skin response (intense itching, swelling and redness) in susceptible individuals; once sensitized contact with very small amount can cause allergic reaction.

**Synergistic materials:** Not available.

**Other important hazards:** CNS depression may result from exposure.

## SECTION 12 — ECOLOGICAL INFORMATION

**Ecotoxicological information:** The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. Do not discharge product unmonitored into the environment.

**Chemical fate information:** There is no data available on the product itself. The main components of this product are expected to biodegrade by atmospheric, aquatic and ground applications.

## SECTION 13 — DISPOSAL CONSIDERATIONS

**Handling for disposal:** Handle according to recommendations listed in Section 7.

**Methods of disposal:** Dispose in accordance with all applicable federal, state and local regulations. Contact your local, state or federal environmental agency for specific rules.

**U.S. RCRA:** For disposal of unused or waste material, check with local, state and federal environmental agencies.

## SECTION 14 — TRANSPORTATION INFORMATION

**U.S. DOT transportation regulation information:** This product is NOT classified as Dangerous Goods under regulations of the U.S. DOT, 49 CFR.

**Transport Canada transportation regulation information:** This product is NOT classified as Dangerous Goods, per regulations of Transport Canada.

## SECTION 15 — REGULATORY INFORMATION

### U.S. Federal Information:

**TSCA information:** All ingredients are listed on the TSCA inventory.

#### **DOT/CERCLA Reportable Quantity (RQ):**

Sodium dodecylbenzenesulfonate = 1000 lb (45.4 kg)

#### **SARA TITLE III:**

*Sec. 302, Extremely Hazardous Substances, 40 CFR 355:* No Extremely Hazardous Substances are present.

*Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes:* Immediate (Acute); Delayed (Chronic). Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

*Sec. 313, Toxic Chemicals Notification, 40 CFR 372:* This material may be subject to TSCA notification requirements, since it contains n-Methyl-2-pyrrolidone, a Toxic Chemical constituent.

**California Proposition 65:** The n-Methyl-2-pyrrolidone component (Cyclic Amide) is listed on Proposition 65 as a chemical that can cause developmental harm.

### **CANADIAN FEDERAL REGULATION INFORMATION:**

**Canadian DSL/NDSL Inventory status:** Components of this product are listed on the DSL Inventory.

**Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:** No component of this product is on the CEPA Priorities Substances Lists.

**SECTION 15 — REGULATORY INFORMATION (Continued)**

**Canadian Federal Information (continued):**

**Canadian WHMIS classification and symbols:**

**Class D2A/D2B:** Material Causing Other Toxic Effects (Toxicity-Irritation-Sensitization)



**SECTION 16 — OTHER INFORMATION**

**Legend:** ACGIH: American Conference of Governmental Industrial Hygienists  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
NIOSH: National Institute of Occupational Safety and Health      HSDB: Hazardous Substances Data Bank  
CAS: Chemical Abstract Services      CFR: Code of Federal Regulations  
DOT: Department of Transportation      EPA: Environmental Protection Agency  
IARC: International Agency for Research on Cancer      MST: Mountain Standard Time  
N/Ap: not applicable      N/Av: not available  
OSHA: Occupational Safety and Health Administration      NTP: National Toxicology Program  
RCRA: Resource Conservation and Recovery Act      PEL: Permissible Exposure Limit  
SARA: Superfund Amendments & Reauthorization Act      TLV: Threshold Limit Values  
TSCA: Toxic Substance Control Act      TWA: Time Weighted Average  
RTECs: Registry of Toxic Effects of Chemical Substances

**Disclaimer:**

The information in this MSDS was obtained from sources we believe are reliable. We believe the information was accurate at the time it was compiled. However, no warranty, express or implied, including, without limitation, any warranty of **fitness for a particular purpose or merchantability**, is made as to the accuracy, reliability or completeness of this information, and all such warranties are disclaimed. The conditions of storing, handling and use being beyond the manufacturer's control, it is the sole responsibility of the user to determine all appropriate precautions for the safe handling and use of this product. The information contained herein pertains only to this product and not to its use in combination with any other materials. It is the user's responsibility to comply with all applicable federal, state, and local laws. Manufacturer disclaims all liability for incidental or consequential damages arising out of or in connection with the use of, or inability to use, this product.

**Prepared by:** BK Enterprises  
**Telephone No.:** 303-865-8800  
**Preparation date:** July 18, 2007

**END OF DOCUMENT**