



## Product Data Sheet

Product Name: **Metal Safe Graffiti Remover**

Description/Uses: Metal Safe Graffiti Remover is a strong, fast acting liquid graffiti remover. It is recommended for the removal of graffiti from pre-finished metal or powder coated products such as overhead doors, color bonded fencing, mail boxes, signal boxes, traffic signs, etc.

(Note: On metal signs Metal Safe Graffiti Remover may be too harsh and printers ink could dissolve. Sign Safe Graffiti Remover, Marker Graffiti Remover, or General Purpose Graffiti Remover may be more appropriate products to use on metal signs).

Surface Preparation: Wash the surface with water prior to applying the Metal Safe Graffiti Remover to the surface.

### Application Information

Method: Use product full strength, do not dilute. Wet down the surface with water, then apply Metal Safe Graffiti Remover to the affected area with a rag or spraying. Allow the product to penetrate the surface for 60 seconds and then agitate with a cloth or “OOO” steel wool. Wipe off with a clean cloth and wash down with water.

### Specifications

Coverage Rate: Up to 50-100 Square Ft/Quart depending upon graffiti area, surface porosity, surface texture, and method of application.

DOT Shipping Class: N/A

Hazardous Class: N/A

Freight Class: 55

UN NO: N/A

Shelf Life: 2 years

Storage: Refer to section 7 in the MSDS (Material Safety Data Sheet)

### **Safety Information**

**Safety Directions:** Always wear protective goggles, clothes, and chemical resistant gloves when using Metal Safe Graffiti Remover. Metal Safe Graffiti Remover may produce severe burns. Do not breathe vapors. Metal Safe Graffiti Remover is flammable.

**First Aid:** If there is an emergency contact a doctor and/or call 911 for emergency assistance. If swallowed, do not induce vomiting. If Metal Safe Graffiti Remover gets in the eyes, hold eyelids apart and flush eyes continuously with running water for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

### **Emergency Procedure**

**Spills/Leaks:** Cover with inert absorbent (sand, earth, vermiculite, etc.) and transfer to container for safe disposal.

**Fire:** Use water fog or fine water spray. Emergency workers should wear full protective clothing including goggles, breathing apparatus and chemical resistant gloves. Prevent spillage from entering natural waters. Additional information is listed in the MSDS (Material Safety Data Sheet).